

CEBORA P50 SERIES TORCH

- 50A Rated
- 60% Duty Cycle
- 10 - 15mm Cutting Thickness
- Air Cooled
- 4.5 - 5.0 bar, 65 - 75psi Gas Pressure

- 120L/min, 250scfh Gas Flow
- Electrode to Tip Pilot
- HF Ignition
- 90 sec Post Flow

ITEM	DESCRIPTION	QTY
CBR50-60-CC1	Cebora Style P50 Plasma Torch - 6m	1




RELATED PARTS

TORCH HEAD




ITEM	DESCRIPTION	PACK QTY
CBR1352	Torch Head to Suit P50	1

SWIRL RING



ITEM	DESCRIPTION	PACK QTY
C1510	Swirl Ring	1

RETAINING CAP



ITEM	DESCRIPTION	PACK QTY
C5.710.121	Retaining Cap	1

HANDLE KIT



ITEM	DESCRIPTION	PACK QTY
PW5014	Plasma Torch Handle Kit - CBR50 & CBR70	1

SPACERS/STAND OFF GUIDE



ITEM	DESCRIPTION	PACK QTY
51806	Cutting Guide	1
C1405	Double Pointed Spacer	1
C1394	Spacer Spring	1

CUTTING TIPS



ITEM	DESCRIPTION	PACK QTY
C1309	Cutting Tip 0.9mm, 35A	5
C1366	Cutting Tip Long 0.9mm, 35A	5
C1304	Cutting Tip 1.0mm, 50A	5
C1305	Cutting Tip Conical 1.0mm, 50A	5
C1306	Cutting Tip Long Conical 1.0mm, 50A	5

ELECTRODES



ITEM	DESCRIPTION	PACK QTY
C1521	Standard Electrode	5
C1518	Long Electrode	5